



LOW PROFILE PARTS HOPPER - HOP-LP

APPROX WEIGHT: 293.39 lbs.
DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!!

*** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE ***

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON



DIMENSION TOLERANCE $\pm 1/4$ "

STANDARD FEATURES

MODEL NUMBER: HOP-LP
CAPACITY: 2,000 LBS.
VOLUME: 1/2 CUBIC YARD
OVERALL WIDTH: 48 7/16"
OVERALL LENGTH: 54 1/16"
OVERALL HEIGHT: 34"
WORK ENVELOPE: 48 7/16" X 57 11/16" X 55 3/4"
CHUTE SIZE: 48 7/16" X 44 11/16" X 13 3/4"
FORK POCKETS: 7"W X 2"H, 21 5/8" ON CENTER
1-SWIVEL 4" X2"
GLASS FILLED NYLON CASTERS W/ LOCK
1- SWIVEL 4"X2"
GLASS FILLED NYLON CASTER
2- RIGID 4"X2"
GLASS FILLED NYLON CASTERS
DURABLE BAKED IN POWDER COATED BLUE FINISH

SPECIAL FEATURES

NONE

APPROX. WEIGHT / LOST LOAD = 293.39
MINIMUM EFFECTIVE THICKNESS =
VERTICAL CENTER OF GRAVITY = 8 1/8"
HORIZONTAL CENTER OF GRAVITY = 17 11/16"

NEVER EXCEED LOAD CENTER
RATING PER FORKTRUCK
MANUFACTURERS GUIDELINES.
DO NOT USE THIS FORK TRUCK
ATTACHMENT IF LOAD WILL EXCEED
FORK TRUCK MANUFACTURER'S
LOAD CENTER RATING

APPROVAL

I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.
UNITS REQUIRING APPROVAL DRAWINGS OR MODIFIED ARE NON-RETURNABLE
[] As drawn [] As marked

Signed: _____ Date: _____

Printed Name: _____

LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING

DISTRIBUTOR'S NAME:		P.O.#
VESTIL MANUFACTURING		X
DRAWN BY: CA		W.O.#
DATE: 2/20/2013		X
REFERENCE: X	SCALE: 1:15	SALES: X
QUOTED LEAD TIME: X	QUOTE # X	FILE NAME:
		37-007-031